

1445001201



1445 215/110-240/5/6/IP67/-O-/M24-12.5
/TW-HALOGENFREE/850



Termination

Optic	Clear
Type of through wiring	3-pole
Type of blind-plug	M20-Polyamide
Number of cable glands	2
Number of blind plugs	2
Type of cable gland	M24-Brass

Light data

Number of lamps	2
Lamp power (W)	15
Light source	LED
Lamp code supplied light source	CRI > 80, 5000K
Nominal lumen value (lm)	5000

Technical data

Maximum ambient temperature (°C)	45
IP classification	67
Minimum ambient temperature (°C)	-25

Ballast/Driver

Type of ballast/driver	High frequency
Number of ballast/driver	1

Electrical data

Maximum voltage +10% (V)	240
Maximum frequency +5% (Hz)	60
Minimum frequency -5% (Hz)	50
Minimum Voltage -10% (V)	110
Electromagnetic compatibility	EMC1

Dimensions

Height (mm)	116
Net weight (kg)	3,6
Width (mm)	193
Length (mm)	692
Gross weight (kg)	4,223

Body

Colour of body	White
Body material	Zinc coated steel
Body colour code	RAL 9016

Optic

Material of diffuser	Polycarbonate
----------------------	---------------

Remarks

Remarks	Cable entry: 2xM24x1.5 brass D10-12.5mm MGCG+2xbli
---------	---

1445001201



1445 215/110-240/5/6/IP67/-O-/M24-12.5
/TW-HALOGENFREE/850



Drawings

