(4) Heater ---------- 1 Set/Unit

. Type : Electric heating type

. Heating capacity : 18 kW (15,500kcal/h)

(5) Fan with motor ---------- 1 Set/Unit

. Type : Double suction multi blade Centrifugal fan

. Model : DDM 9-9

. Discharge Type : Duct connection type

. Air flow rate : 1,400 ㎥/h(External static pressure : 350Pa)

. Motor Output : 0.55kW x 4Poles

. Max Running Current : 2.5 A

(6) Control & Safety Devices ---------- 1 Lot/Unit

. 1 piece - Dual pressure switch

. High pressure setting : Cut-out 24 bar
: Cut-in Manual reset

. Low pressure setting : Cut-out 2.5 bar
: Cut-in 3.5 bar

. 1 piece - High pressure gauge : 60ø, 0 ~ 3.5 MPa

. 1 piece - Low pressure gauge : 60ø, -0.1~ 1.5 MPa

(7) Charging chemicals ---------- 1 Lot/Unit

. 8 kg - Refrigerant R-404A

. 1.8 Liter - Polyolester oil 160PZ

(8) Air- filter ---------- 1 Set/Unit

. Type : Washable Vinyl Chloride Fiber

. Size : W320 x H210 (5t)

(9) Other components and accessories, fitted in/on PAC unit --------- 1 Lot/Unit

a) On internal piping lines

. 1 piece - Expansion valve

. 1 piece - Filter drier 5/8" on liquid line

. 1 piece - Service angle valve 5/8" on liquid line

. 1 piece - Solenoid valve 5/8"(220V) on liquid line