

CTF & TF LIGHT TOWERS

CTF & TF

CTF and TF light towers are the most basic models of the Generac® Tower Light range. These static light towers are extremely practical and easy to be used, ensuring a good level of illumination for small to medium sized areas. The CTF variants of 5.5, 7 and 9 meters are ideal for applications in containers, mobile offices, temporary dormitories and power factories. The 5 meters CTF is suitable for application on road trailer. All these models are also perfect for civil protection use.



TF 5,5

TF 7

TECHNICAL DATA			
Minimum dimensions (mm)	Lenght x Width x Height	350 x 400 x 1900	350 x 400 x 2350
Maximum dimensions (mm)	Lenght x Width x Height	1840 x 1500 x 5500	2020 x 1500 x 7000
Dry weight (kg)		64	75
Lifting system	M:Manual / H:Hydraulic	M	M
Lamps power (W)		4 x 500	2 x 1500
Lamps type	HL:Halogen / LD:LED	HL	HL
Total lumen (Lm)		44000	66000
Illuminated area (m²)		625	1200
Inlet plug	A/V/Hz	16/220/50 - 16/240/60	16/220/50 - 16/240/60
Wind speed resistance (km/h)		80	80



CTF 5 MH

CTF 5 L

TECHNICAL DATA			
Minimum dimensions (mm)	Lenght x Width x Height	1170 x 420 x 1700	1230 x 480 x 2040
Maximum dimensions (mm)	Lenght x Width x Height	1170 x 420 x 5000	1230 x 480 x 5000
Dry weight (kg)		135	145
Lifting system	M:Manual / H:Hydraulic	M	M
Mast rotation (°)		360	360
Lamps power (W)		4 x 400	4 x 185
Lamps type	MH:MetalHalide / LD:LED	MH	LD
Total lumen (Lm)		144000	93000
Illuminated area (m²)		1600	2100
Inlet plug	A/V/Hz	16/220/50 - 16/240/60	16/220/50 - 16/240/60
Wind speed resistance (km/h)		80	80



CTF 5,5

CTF 7

CTF 9

TECHNICAL DATA				
Minimum dimensions (mm)	Lenght x Width x Height	260 x 280 x 1900	260 x 280 x 2380	280 x 280 x 2500
Maximum dimensions (mm)	Lenght x Width x Height	310 x 550 x 5500	350 x 1060 x 7000	350 x 1060 x 9000
Dry weight (kg)		67	85	93
Lifting system	M:Manual / H:Hydraulic	M	M	M
Mast rotation (°)		360	360	360
Lamps power (W)		4 x 500	4 x 1000	4 x 1500
Lamps type	HL:Halogen / LD:LED	HL	HL	HL
Total lumen (Lm)		44000	88000	132000
Illuminated area (m²)		625	1500	2000
Inlet plug	A/V/Hz	16/220/50 - 16/240/60	32/220/50 - 32/240/60	32/220/50 - 32/240/60
Wind speed resistance (km/h)		80	80	80