


Manufacturing date	04.06.2010 -
Product description	Explosion protected portable luminary
ATEX & IECEx marking	 Ex II 2 G Ex e mb IIC T3 Gb Ex II 2 D Ex tb IIIC T90°C Db (subject to type of socket)
Temperature classification	T3 (internal) T90°C (external)
Operating temperature	-20°C ... +40°C
Light source	2 CFL (36 W compact fluorescent tube with explosion protection)
Light emitted at source	up to 5800 lm
Luminous flux	up to 2850 lm
Colour temperature	4000 K +/- 5 %
Colour rendering index	>80
Photobiological safety	Exempt group (No marking required, safe in normal use)
Supply Voltage	110-230VAC +/- 6%, 50/60Hz or 24VAC /DC +/- 6%, 0/50/60Hz or 42VAC /DC +/- 6%, 0/50/60Hz
Supply Current (typical)	230V ~0,3 A 42V ~1,5 A 110V ~0,6 A 24V ~2,5 A
Electrical class	Class 1 (230 & 110 VAC), Class 3 (24V & 42 V)
Power consumption	< 60 W
Cable	Standard cable H07BQ-F
Plug and socket	2P + Earth (110-230V) 2P+E, 3P, 2P (24-42V)
Enclosure	Dissipative materials (PC & TPE)
Ingress protection	IP66 (A-VERSION) IP54-IP66 (C-version, IP rating is subject to type of socket)
Weight (without cable, socket and plug)	2,7 kg
Accessories	SLAM Click'n Fix magnetic fixing system Protective film
Warranty	You will find detailed warranty conditions from www.atexor.com/warranty



	Dimensions / mm	
Product model	L	Ø
SLAM® Hornet 236 A & C	865	115

