


TRACK CABLES

FLEXIDRUM® T 210

High speed continuously flexible PUR halogen-free control cable,
DIN VDE 0,6/1 kV, UL/CSA 600/1000 V



Part no.	No. of cores x cross section n x mm ²	Outer-Ø ca. mm ± 10%	Copper weight kg/km	Cable weight approx. kg/km	AWG no. *)
04110G41020A18	2x1	6,7	19,2	50	18
04110G40031A18	3 G 1	6,9	28,8	60	18
04110G40041A18	4 G 1	7,1	38,4	75	18
04110G40051A18	5 G 1	7,7	48	90	18
04110G40071A18	7 G 1	9	67,2	125	18
04110G40121A18	12 G 1	11	115,2	185	18
04110G40181A18	18 G 1	13	172,8	270	18
04110G40251A18	25 G 1	15,7	240	370	18
04110G40341A18	34 G 1	17,4	326,4	490	18
04110G40501A18	50 G 1	20,5	480	695	18
04110G40611A18	61 G 1	22,9	586,6	870	18
04110G41020A16	2x1,5	7,3	28,8	50	16
04110G40031A16	3 G 1,5	7,4	43,2	80	16
04110G40041A16	4 G 1,5	7,9	57,6	100	16
04110G40051A16	5 G 1,5	8,6	72	120	16
04110G40071A16	7 G 1,5	10,1	100,8	170	16
04110G40121A16	12 G 1,5	12,4	172,8	260	16
04110G40181A16	18 G 1,5	14,5	259,2	375	16
04110G40251A16	25 G 1,5	18	360	510	16
04110G40341A16	34 G 1,5	19,9	489,6	690	16
04110G40501A16	50 G 1,5	23,4	720	975	16
04110G40611A16	61 G 1,5	26	878,4	1200	16
04110G41020A14	2x2,5	8,3	48	78	14
04110G40031A14	3 G 2,5	8,8	72	125	14
04110G40041A14	4 G 2,5	10,2	96	160	14
04110G40051A14	5 G 2,5	11,1	120	190	14
04110G40071A14	7 G 2,5	13,2	168	270	14
04110G40121A14	12 G 2,5	15,8	288	420	14
04110G40181A14	18 G 2,5	18,6	432	620	14
04110G40251A14	25 G 2,5	22,8	600	830	14
04110G40031A12	3 G 4	10,5	115,2	180	12
04110G40041A12	4 G 4	11,4	153,6	230	12
04110G40051A12	5 G 4	12,5	192	290	12
04110G40031A10	3 G 6	12,4	172,8	260	10
04110G40041A10	4 G 6	13,8	230,4	330	10
04110G40051A10	5 G 6	15,1	288	420	10
04110G40031A08	3 G 10	15,6	288	430	8
04110G40041A08	4 G 10	17,3	384	360	8
04110G40051A08	5 G 10	19,3	480	520	8
04110G40031A06	3 G 16	18,2	460,8	620	6
04110G40041A06	4 G 16	20,2	614,4	800	6
04110G40051A06	5 G 16	22,4	768	1000	6
04110G40041A04	4 G 25	25,2	960	1200	4
04110G40051A04	5 G 25	25,7	1200	1500	4
04110G40041A02	4 G 35	26,8	1344	1620	2
04110G40051A02	5 G 35	28,7	1680	2030	2
04110G40051A01	4 G 50	34	1920	2280	1

Other dimension and colours available on request.