

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

SECTION 1. IDENTIFICATION

Product name : Bectron® 239 Thinner

Manufacturer or supplier's details

Company : ELANTAS PDG, INC.
5200 North 2nd Street
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : www.elantas.com

E-mail address : Todd.Thomas@altana.com

Emergency telephone number : INFOTRAC - 1-800-535-5053

Recommended use of the chemical and restrictions on use

Recommended use : Resin Reducer

Restrictions on use : Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 3

Skin irritation : Category 2

Serious eye damage : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

Precautionary statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Petroleum Naphtha / Hydroxyacid Ester Blend

Hazardous components

Component	CAS-No.	Concentration (%)
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 95 - < 96
Hydroxy acetic acid butyl ester (Butyl glycolate)	7397-62-8	>= 5 - < 6

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.
No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

Engineering measures : Use with adequate ventilation.
All application areas should be ventilated in accordance with applicable OSHA regulations. (29 CFR 1910.94)

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: 81 °F (27 °C) Method: ISO 1523 Information taken from reference works and the literature.
Evaporation rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.76 g/cm ³ (68 °F (20 °C)) Method: 1 (20°C coating pycnometer)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Hazardous decomposition products	: Carbon monoxide in a fire. Nitrogen oxides in a fire.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**64742-49-0 Naphtha (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

7397-62-8 Hydroxy acetic acid butyl ester (Butyl glycolate):

Acute oral toxicity : LD50 (Rat): 4,595 mg/kg

Skin corrosion/irritation**Product:**

Remarks: Extremely corrosive and destructive to tissue.

Components:**7397-62-8 Hydroxy acetic acid butyl ester (Butyl glycolate):**

Species: Rabbit

Result: Moderate skin irritation

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Components:**7397-62-8 Hydroxy acetic acid butyl ester (Butyl glycolate):**

Species: Rabbit

Result: Corrosive to eyes

Respiratory or skin sensitisation**Components:****7397-62-8 Hydroxy acetic acid butyl ester (Butyl glycolate):**

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

GLP: yes

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****64742-49-0 Naphtha (petroleum), hydrotreated light:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 11.4 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia pulex (Water flea)): 3 mg/l
aquatic invertebrates Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of
Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a
Class I or Class II ODS as defined by the U.S. Clean Air Act
Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological : No data available
information

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste : D001: Ignitable
Code(s)

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulation****IATA-DGR**

UN/ID No. : UN 1263
Proper shipping name : Paint related material
Class : 3
Packing group : III
Labels : Flammable liquid
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1263
Proper shipping name : PAINT RELATED MATERIAL
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 1263
Proper shipping name : Paint related material
Class : 3
Packing group : III
Labels : Flammable liquid
ERG Code : 128
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Bectron® 239 Thinner

Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard
Fire Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

US State Regulations**Massachusetts Right To Know**

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know

Naphtha (petroleum), hydrotreated light	64742-49-0
Hydroxy acetic acid butyl ester (Butyl glycolate)	7397-62-8

New Jersey Right To Know

Naphtha (petroleum), hydrotreated light	64742-49-0
Hydroxy acetic acid butyl ester (Butyl glycolate)	7397-62-8

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : NOT APPLICABLE

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Bectron® 239 Thinner


Version 2

Revision Date 05/22/2015

Print Date 05/22/2015

The components of this product are reported in the following inventories:

TSCA	: We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720.30(h).
Section 4 / 12(b)	: Not applicable
Section 5	: Not applicable
DSL	: We certify that all of the components of this product are listed on the DSL.

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 05/22/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.