



MULTIPURPOSE GROUT PUMP

The Pumpmaster PG-10 is a skid steer grout pump attachment powered by your existing hydraulic powersource and is designed to perform from one job to the next with low maintenance.





The Airplaco PG-10 is a hydraulic grout pump featuring a full-flow ball check manifold and is designed for masonry block fill, piling encasements, pea gravel pumping, concrete leveling and other grouting applications. The PG-10 hydraulic grout pump offers high output without the need for constant lubrication and features a long-life hard chrome cylinder that ensures a long service life. The PG-10 grout pump is a perfect choice for contractors with an existing hydraulic power source, such as a skid steer or hydraulic power pack looking for a durable pump capable of varied applications.



PG-10 SPECIFICATIONS

10 10 01 LOTT TO ATTORE	
Max Output	4 yd3/hr (3 m³)
Max Line Pressure	0 to 400 psi (27 bar)
Material Hopper	7 cu ft (198L)
Material Cylinder	Single 5 in.
Stroke	8 in.
Outlet Size	3 in. HD
Max Aggregate	3/8 in. (9.5 mm)
Max Vertical	50 ft (15 m)
Max Horizontal	150 ft (46 m)
Power Source	Aux. Hydraulics (Min 8 gpm @2500 psi)
Dimensions	29 x 68 x 38 in. (W x L x H)
Hopper Height	36 in (92 cm)
Weight	325 lb (147 kg)
Material Valve	Ball-check

APPLICATIONS:

Machine Base Stabilization Masonry Block Fill **Piling Encasements Pressure Grouting** Slabjack/Mudjack Lifting Void Fill







