

FP340 FEEDER PILLAR SPECIFICATION:


HEIGHT	A	1200
WIDTH	B	1180
DEPTH	C	460
INTERNAL DEPTH		390
DETACHABLE ROOT	D	400
BACKBOARD HEIGHT		1000
BACKBOARD WIDTH		1160
PILLAR WEIGHT		177Kg

SPECIFICATIONS:

FABRICATED FROM 3mm MILD STEEL SHEET
HOT DIPPED GALVANISED
STANDARD FINISH IS POWDER COATED GREY LEATHERETTE (BS693)
18mm THICK EXTERIOR GRADE PLY BACKBOARD,TREATED WITH ANTI-FUNGICIDAL WOOD PRESERVATIVE
REMOVABLE CTR POST BETWEEN DOORS ALLOWING FULL ACCESS TO PILLAR
PILLAR DOORS HINGED VIA INTERNAL STAINLESS STEEL HINGES
EARTH STRAPS FITTED TO PILLAR AND DOORS
FITTED WITH TRIANGULAR HEADED LOCKS
A4 DOCUMENT HOLDER FITTED TO INSIDE OF DOOR
DOOR APERTURES FULLY GASKETED
PILLAR VENTILATION INCORPORATED INTO DESIGN
FITTED WITH DETACHABLE ROOT SECTION, OPEN TO FRONT AND REAR FOR EASY CABLE ENTRY
ROOT SECTION BITUMEN COATED
DESIGNED TO IP54

OPTIONAL EXTRAS:

CAN BE MANUFACTURED IN STAINLESS STEEL
OTHER COLOURS AVAILABLE
PILLAR CAN BE SUPPLIED FOR SURFACE MOUNTING
ANTI GRAFFITI / FLY POSTER TEXTURED FINISH
PADLOCK FACILITY
VANDAL RESISTANT PADLOCK BAR (VRB)
OTHER LOCKS AVAILABLE

REVISION No.	DESCRIPTION OF MODIFICATION	DATE		PART No. A-FP340/3004	DRAWING TITLE:	SHEET 1 of 1	DRAWN DR	CHECKED	APPROVED	DATE 25-09-12
						DRAWING No.				

THIS DRAWING IS THE PROPERTY OF TOFCO CPP AND IS SUPPLIED IN CONFIDENCE.
IT MUST NOT BE USED FOR ANY OTHER PURPOSE OTHER THAN THAT FOR WHICH IT IS
SUPPLIED, AND MUST NOT BE REPRODUCED WITHOUT PERMISSION IN WRITING FROM
THE OWNER