

MICROMASTER MFH200 Specification Sheet

Load Capacity (per panel)	400kg (880lb)
Side Load Capacity (per panel)	200kg (440lb)
Opening Angle	95°
Adjustment Range	
Height	12mm
Sideways	12mm
Compression	6mm
Adjustment Mechanisms	Turnbuckle Linkage, Set Screws
Adjuster Mechanism Material	AISI 316 Stainless Steel – Self locking
Hinge Weight (Door Mount D01 and Frame Mount F01)	1.2kg (2.6lb)
Recycling	Fully Recyclable
Castings/Mouldings	
Material	CD4-MCU Duplex Stainless Steel
Process	Lost wax / Investment cast
Treatment	Heat Treated
Finish	Shot Blast Natural
Machined Components	
Material	AISI 316 Stainless Steel
Finish	Electro polished
Emission Rating	Emission Free (Inert)
Corrosion Resistance	Exceeds ISO 9227 and BS EN 1670:1998
Door Installation Types	
Inset	✓
Overlay	✓
Curtain Wall	✓
Curtain Wall Back-To-Back	✓
Door Mounting Options	
Single Point Fixing	✓
Key Slot Mountain	✓
Surface Screw Mounting	✓
Mortised Insert Mounting	X



FOR MORE INFORMATION GO TO
www.manfredfrank.com