



APPLICATIONS

AUTOL TOP 2000 is a multipurpose green anhydrous calcium grease formulated with mineral and synthetic base oils for longer regreasing intervals.

It contains a special polymer that imparts exceptional adhesive properties and an EP (Extreme Pressure) additive that makes it especially suitable for resistance to loads and vibrations.

AUTOL TOP 2000 is designed to be used in severe operating conditions (salt water, high humidity, shock loads, high pressures with low speeds).

Specific for the lubrication of equipment present on vehicles, on agricultural machinery, on industrial robot and machinery and on boats.

It is suitable for the lubrication of chains, conveyor belts, gears subjected to dynamic stress conditions.

Despite the high base oil viscosity, it can be used in automatic and centralized lubrication systems and by applying a gun.

CUSTOMER ADVANTAGES

- Outstanding adhesivity and resistance to high loads, shocks and vibrations.
- Very high resistance to water washout in presence of water and in wet environments.
- Excellent antirust and anticorrosive properties, it protects the metal components against corrosion in wet and in marine environments.
- Longlife grease, it ensures longer regreasing intervals.

SPECIFICATIONS - APPROVALS

- DIN 51825 KP 2K -30
- ISO 12924 L-XCCHB 2





CHARACTERISTICS

Properties	Method	Unit	Typical
Visual appearance	-	-	omogeneous
Colour	-	-	green
Thickener type		-	anhydrous calcium
Consistency (NLGI grade)	-	-	2
Base oil type		-	mineral + synthetic
Base Oil Viscosity at 40°C	ASTM D 445	mm ² /s	800
Water resistance	DIN 51807	-	0-90
Dropping point	ASTM D 566	°C	150
EMCOR test in distilled water	IP 220	-	0/0
Timken OK load	ASTM D 2509	lbs	55
Temperature range	-	°C	-30/+110

WARNINGS

- Further information are available on the Safety Data Sheet



eni