




Poulies dentées HTD à moyeux amovibles



À MOYEU AMOVIBLE HTD

Matières :

- acier : C 40 UNI 7845

Référence	Dents	Dp	Df	Flasque	5M 15 (E=22)				
					Moyeu	Type	A	B	Masse
34 5M 15 F (....)	34	54,11	57,0	20	1108	1MF	-	-	0,40
36 5M 15 F (....)	36	57,30	60,0	21	1108	1MF	-	-	0,43
38 5M 15 F (....)	38	60,48	66,5	24	1108	1MF	-	-	0,45
40 5M 15 F (....)	40	63,66	71,0	25	1108	1MF	-	-	0,52
44 5M 15 F (....)	44	70,03	75,0	27	1108	1MF	-	-	0,62
48 5M 15 F (....)	48	76,39	83,0	29	1210	4MF	25	59	0,19
56 5M 15 F (....)	56	89,13	93,0	33	1210	4MF	25	70	0,22
64 5M 15 F (....)	64	101,86	106,0	38	1210	4MF	25	80	0,25
72 5M 15 F (....)	72	114,59	-	-	1610	4M	25	92	0,30
80 5M 15 F (....)	80	127,32	-	-	1610	4M	25	92	0,33
90 5M 15 F (....)	90	143,24	-	-	1610	4M	25	92	0,37
112 5M 15 F (....)	112	178,25	-	-	2012	4M	32	110	0,46
136 5M 15 F (....)	136	216,45	-	-	2012	10M	32	110	0,56

(....): Taille moyeu amovible

Matières :

- acier : C 40 UNI 7845 (22 à 72 dents)
- fonte : G 25 UNI 5007 (80 à 144 dents)

Référence	Dents	Dp	Df	Flasque	8M 20 (E=28)					8M 30 (E=38)				
					Moyeu	Type	A	B	Masse	Moyeu	Type	A	B	Masse
22 8M (A) F (....)	22	56,02	60,0	53	1008	2MF	22	-	0,25	1008	2MF	22	-	0,30
24 8M (A) F (....)	24	61,12	66,0	69	1108	2MF	22	-	0,30	1108	2MF	22	-	0,38
26 8M (A) F (....)	26	66,21	70,0	61	1108	2MF	22	-	0,36	1108	2MF	22	-	0,45
28 8M (A) F (....)	28	71,30	75,0	79	1108	2MF	22	-	0,44	1210	2MF	25	-	0,55
30 8M (A) F (....)	30	76,39	83,0	73	1108	2MF	22	-	0,53	1615	1MF	-	-	0,45
32 8M (A) F (....)	32	81,49	87,0	76	1610	2MF	25	-	0,42	1615	1MF	-	-	0,60
34 8M (A) F (....)	34	86,58	91,0	66	1610	2MF	25	-	0,55	1615	1MF	-	-	0,75
36 8M (A) F (....)	36	91,67	97,0	68	1610	2MF	25	-	0,68	1615	1MF	-	-	1,00
38 8M (A) F (....)	38	96,77	102,0	70	1610	2MF	25	-	0,80	1615	1MF	-	-	1,15
40 8M (A) F (....)	40	101,86	106,0	77	1610	2MF	25	-	1,00	1615	1MF	-	-	1,35
44 8M (A) F (....)	44	112,05	120,0	75	2012	4MF	32	92	1,20	2012	2MF	32	-	1,35
48 8M (A) F (....)	48	122,23	128,0	78	2012	4MF	32	96	1,60	2012	2MF	32	-	1,75
56 8M (A) F (....)	56	142,60	150,0	85	2012	4MF	32	110	2,40	2012	2MF	32	-	3,75
64 8M (A) F (....)	64	162,97	168,0	90	2012	5MF	32	110	2,70	2517	4MF	45	125	4,25
72 8M (A) F (....)	72	183,35	192,0	97	2012	5MF	32	110	3,30	2517	5MF	45	125	4,30
80 8M (A) F (....)	80	203,72	-	-	2012	5M	32	110	3,50	2517	5M	45	125	4,60
90 8M (A) F (....)	90	229,18	-	-	2012	5M	32	110	3,65	2517	5M	45	125	5,00
112 8M (A) F (....)	112	285,21	-	-						2517	5M	45	125	6,20
144 8M (A) F (....)	144	366,69	-	-						2517	6M	45	125	9,20

(A): Largeur de la courroie exprimée en mm, soit : 20 et 30

(....): Taille moyeu amovible





Matières :


- acier : C 40 UNI 7845 (22 à 72 dents)
- fonte : G 25 UNI 5007 (80 à 144 dents)

Référence	Dents	Dp	Df	Flasque	8M 50 (E=60)					8M 50 (E=60)				
					Moyeu	Type	A	B	Masse	Moyeu	Type	A	B	Masse
28 8M (A) F (....)	28	71,30	75,0	79	1210	2MF	25	-	0,75	1008	2MF	22	-	0,30
30 8M (A) F (....)	30	76,39	83,0	73	1615	2MF	38	-	0,65	1108	2MF	22	-	0,38
32 8M (A) F (....)	32	81,49	87,0	76	1615	2MF	38	-	0,85	1108	2MF	22	-	0,45
34 8M (A) F (....)	34	86,58	91,0	66	1615	2MF	38	-	1,05	1615	3MF	38	-	1,45
36 8M (A) F (....)	36	91,67	97,0	68	1615	2MF	38	-	1,30	1615	3MF	38	-	1,85
38 8M (A) F (....)	38	96,77	102,0	70	1615	2MF	38	-	1,60	1615	3MF	38	-	2,25
40 8M (A) F (....)	40	101,86	106,0	77	2012	3MF	32	-	1,25	2012	3MF	32	-	1,75
44 8M (A) F (....)	44	112,05	120,0	75	2012	3MF	32	-	1,70	2012	3MF	32	-	2,30
48 8M (A) F (....)	48	122,23	128,0	78	2012	3MF	32	-	2,30	2517	3MF	45	-	2,65
56 8M (A) F (....)	56	142,60	150,0	85	2517	3MF	45	-	3,40	2517	3MF	45	-	4,50
64 8M (A) F (....)	64	162,97	168,0	90	2517	3MF	45	-	5,00	2517	3MF	45	-	6,75
72 8M (A) F (....)	72	183,35	192,0	97	2517	8MF	45	125	6,75	3020	3MF	51	-	8,00
80 8M (A) F (....)	80	203,72	-	-	3020	3M	51	-	8,75	3020	3M	51	-	10,00
90 8M (A) F (....)	90	229,18	-	-	3020	8M	51	160	8,75	3020	3M	51	-	10,75
112 8M (A) F (....)	112	285,21	-	-	3020	8M	51	170	12,00	3020	8M	51	170	15,00
144 8M (A) F (....)	144	366,69	-	-	3020	9M	51	170	15,25	3525	8M	65	198	22,00
168 8M (A) F (....)	168	427,81	-	-	3525	10M	65	198	16,50	3525	9M	65	198	23,00
192 8M (A) F (....)	192	488,92	-	-	3525	10M	65	198	22,00	3525	9M	65	198	29,00
144 8M (A) F (....)	144	366,69	-	-						2517	6M	45	125	9,20

(A): Largeur de la courroie exprimée en mm, soit : 50 et 85

(....): Taille moyeu amovible





Poulies dentées HTD à moyeux amovibles

À MOYEU AMOVIBLE HTD

Matières :

- acier : C 40 UNI 7845 (28 à 48 dents)
- fonte : G 25 UNI 5007 (56 à 216 dents)

Référence	Dents	Dp	Df	Flasque	14M 40 (E=54 - B=170)					14M 55 (E=70 - B=170)				
					Moyeu	Type	A	B	Masse	Moyeu	Type	A	B	Masse
28 14M (A) F (....)	28	124,78	128,0	153	2012	3MF	32	-	2,00	2012	3MF	32	-	2,20
29 14M (A) F (....)	29	129,23	138,0	154	2012	3MF	32	-	2,40	2012	3MF	32	-	2,75
30 14M (A) F (....)	30	133,69	138,0	154	2012	3MF	32	-	2,65	2517	3MF	45	-	2,70
32 14M (A) F (....)	32	142,60	154,0	160	2012	3MF	32	-	3,40	2517	3MF	45	-	3,65
34 14M (A) F (....)	34	151,52	160,0	166	2517	3MF	45	-	3,90	2517	3MF	45	-	4,55
36 14M (A) F (....)	36	160,43	168,0	168	2517	3MF	45	-	4,80	2517	3MF	45	-	5,20
38 14M (A) F (....)	38	169,34	183,0	172	2517	3MF	45	-	5,40	2517	3MF	45	-	6,20
40 14M (A) F (....)	40	178,25	188,0	162	2517	3MF	45	-	6,00	2517	3MF	45	-	7,00
44 14M (A) F (....)	44	196,08	211,0	175	3020	3MF	51	-	7,80	3020	3MF	51	-	8,50
48 14M (A) F (....)	48	213,90	226,0	180	3020	3MF	51	-	9,40	3020	3MF	51	-	10,50
56 14M (A) F (....)	56	249,55	256,0	182	3020	3MF	51	-	10,80	3020	3MF	51	-	12,50
64 14M (A) F (....)	64	285,21	296,0	184	3020	8MF	51	-	13,40	3020	8MF	51	-	14,50
72 14M (A) F (....)	72	320,86	-	-	3020	8M	51	-	15,20	3020	8M	51	-	16,25
80 14M (A) F (....)	80	356,51	-	-	3020	9M	51	-	16,00	3020	9M	51	-	17,50
90 14M (A) F (....)	90	401,07	-	-	3020	9M	51	-	17,80	3020	9M	51	-	20,00
112 14M (A) F (....)	112	499,11	-	-	3020	9M	51	-	25,60	3020	9M	51	-	28,50
144 14M (A) F (....)	144	641,71	-	-	3020	9M	51	-	33,00	3020	9M	51	-	36,25
168 14M (A) F (....)	168	748,66	-	-	3020	9M	51	-	44,00	3020	9M	51	-	49,00
192 14M (A) F (....)	192	855,62	-	-	3020	9M	51	-	49,00	3020	9M	51	-	53,00
216 14M (A) F (....)	216	962,57	-	-	3020	9M	51	-	55,00	3535	10M	89	-	66,00

(A): Largeur de la courroie exprimée en mm, soit : 40 et 55 (....): Taille moyeu amovible

Matières :

- acier : C 40 UNI 7845 (28 à 48 dents)
- fonte : G 25 UNI 5007 (56 à 216 dents)

Référence	Dents	Dp	Df	Flasque	14M 85 (E=102)					14M 115 (E=133)				
					Moyeu	Type	A	B	Masse	Moyeu	Type	A	B	Masse
28 14M (A) F (....)	28	124,78	128,0	153	2517	3MF	45	-	2,75	2517	3MF	45	-	3,75
29 14M (A) F (....)	29	129,23	138,0	154	2517	3MF	45	-	3,50	2517	3MF	45	-	4,00
30 14M (A) F (....)	30	133,69	138,0	154	2517	3MF	45	-	3,75	2517	3MF	45	-	5,00
32 14M (A) F (....)	32	142,60	154,0	160	2517	3MF	45	-	4,75	2517	3MF	45	-	6,75
34 14M (A) F (....)	34	151,52	160,0	166	2517	3MF	45	-	5,75	2517	3MF	45	-	6,75
36 14M (A) F (....)	36	160,43	168,0	168	3020	3MF	51	-	5,75	3020	3MF	51	-	7,00
38 14M (A) F (....)	38	169,34	183,0	172	3020	3MF	51	-	6,75	3020	3MF	51	-	8,50
40 14M (A) F (....)	40	178,25	188,0	162	3020	3MF	51	-	8,00	3020	3MF	51	-	9,25
44 14M (A) F (....)	44	196,08	211,0	175	3020	3MF	51	-	11,75	3030	3MF	76	-	14,00
48 14M (A) F (....)	48	213,90	226,0	180	3020	3MF	51	-	15,00	3030	3MF	76	-	17,25
56 14M (A) F (....)	56	249,55	256,0	182	3525	3MF	65	-	22,50	3535	3MF	89	-	24,75
64 14M (A) F (....)	64	285,21	296,0	184	3525	8MF	65	190	26,00	3535	8MF	89	190	29,00
72 14M (A) F (....)	72	320,86	-	-	3525	8M	65	190	25,50	3535	8M	89	190	29,00
80 14M (A) F (....)	80	356,51	-	-	3525	9M	65	190	29,25	3535	9M	89	190	33,00
90 14M (A) F (....)	90	401,07	-	-	3525	9M	65	190	30,75	3535	9M	89	190	36,50
112 14M (A) F (....)	112	499,11	-	-	3525	9M	65	190	39,50	3535	9M	89	190	46,00
144 14M (A) F (....)	144	641,71	-	-	3525	9M	65	190	51,00	4040	9M	102	230	68,00
168 14M (A) F (....)	168	748,66	-	-	3525	9M	65	190	61,00	4040	9M	102	230	82,60
192 14M (A) F (....)	192	855,62	-	-	4040	7M	102	230	86,00	4040	9M	102	230	96,00
216 14M (A) F (....)	216	962,57	-	-	4040	7M	102	230	91,00	4040	9M	102	230	107,00


(A): Largeur de la courroie exprimée en mm, soit : 85 et 115 (....): Taille moyeu amovible

- Matières : • acier : C 40 UNI 7845 (28 à 48 dents)
• fonte : G 25 UNI 5007 (56 à 216 dents)


Référence	Dents	Dp	Df	Flasque	14M 170 (E=187)				
					Moyeu	Type	A	B	Masse
38 14M (A) F (....)	38	169,34	183,0	172	3030	3MF	76	-	11,70
40 14M (A) F (....)	40	178,25	188,0	162	3030	3MF	76	-	13,00
44 14M (A) F (....)	44	196,08	211,0	175	3535	3MF	89	-	40,00
48 14M (A) F (....)	48	213,90	226,0	180	3535	3MF	89	-	19,00
56 14M (A) F (....)	56	249,55	256,0	182	3535	3MF	89	-	28,50
64 14M (A) F (....)	64	285,21	296,0	184	4040	3MF	102	-	41,00
72 14M (A) F (....)	72	320,86	-	-	4040	8M	102	230	46,90
80 14M (A) F (....)	80	356,51	-	-	4040	8M	102	230	48,00
90 14M (A) F (....)	90	401,07	-	-	4040	9M	102	230	52,50
112 14M (A) F (....)	112	499,11	-	-	5050	9M	127	265	74,50
144 14M (A) F (....)	144	641,71	-	-	5050	9M	127	265	91,00
168 14M (A) F (....)	168	748,66	-	-	5050	9M	127	265	116,00
192 14M (A) F (....)	192	855,62	-	-	5050	9M	127	265	134,00
216 14M (A) F (....)	216	962,57	-	-	5050	9M	127	265	146,50

(A): Largeur de la courroie exprimée en mm, soit : 170


(....): Taille moyeu amovible




10M - Type évidé non flasqué en fonte




3MF - Type plein flasqué en acier ou fonte




6M - Type évidé non flasqué en fonte



8M - Type allégé non flasqué en fonte



8MF - Type allégé flasqué en fonte



9M - Type évidé non flasqué en fonte