



1 4243 AIR CAULKING GUN

- For the automotive workshop
- Accepts standard size 215 x 50mm cartridges

Bore size	50mm
Tube length	215mm
Operating air pressure	30-60psi (2.1- 4.1bar)
Average air consumption	6.0cfm (170L/min)
Minimum hose size	3/8" I.D
Air Inlet	1/4" BSP
Weight	1.1kg

Stock
No.
22301



2 4244A AIR UNDERBODY COATING GUN

- Easy to use air underbody coating gun (Schutz)
- Fits 1 litre "Schutz" type canisters

Canister thread (Schutz type)	M42 x 3P
Tube length	215mm
Operating air pressure	90 PSI (6.2bar)
Average air consumption	8.0 CFM (227 L/min)
Minimum hose size	3/8" I.D
Air Inlet	1/4" BSP
Weight	1.4kg

Stock
No.
55109



3 4997 400cc HEAVY DUTY AIR GREASE GUN

- Continuous flow
- Accepts bulk or standard 400g cartridges
- 360° adjustable handle
- Rigid delivery tube

Operating air pressure	30-110psi (2.1-7.6bar)
Average air consumption	2400-4500psi (166-414bar)
Minimum hose size	3/8" I.D
Air Inlet	1/4" BSP
Weight	1.5kg

Stock
No.
71837



4 4297 400cc AIR GREASE GUN

- Accepts bulk, standard or pump 400g cartridges
- 360° adjustable handle
- Rigid and flexible delivery tube

Operating air pressure	30-110psi (2.1-7.6bar)
Average air consumption	1200-4500psi (83-414bar)
Minimum hose size	3/8" I.D
Air Inlet	1/4" BSP
Weight	1.5kg

Stock
No.
33785



5 4287A 750ml AIR PARAFFIN/WASHING GUN

- Sprays a wide range of oils, cleaning agents and rust proofing liquids
- Fitted with adjustable nozzle

Operating air pressure	40-90psi (2.8-6.2bar)
Air inlet	1/4" BSP
Weight	0.5kg

Stock
No.
43135



6 4288B PISTOL-GRIP AIR INFLATOR

Pistol-grip with dial. Suitable for use with motor vehicles, cycles, dinghies, etc. Clip-on connector. Maximum inflation pressure 8 BAR (115psi). Dial reads 0-12bar and 0-170psi (for guidance only). Display packed.

The pressure dial on this model is for guidance only and should be checked with a tyre pressure gauge to BS EN12645

Stock
No.
10604



7 4288 PISTOL-GRIP AIR INFLATOR

Pistol-grip with dial. Suitable for use with motor vehicles, cycles, dinghies, etc. Clip-on connector. Dial reads 0-10bar and 0-140psi. Carton packed.

The pressure dial on this model is for guidance only and should be checked with a tyre pressure gauge to BS EN12645:1999

Stock
No.
27871